



- 1**  $\frac{7}{16}$ " x  $\frac{5}{8}$ " RF MONEL SEAL

**2** NEOPRENE SEAL (FOR SOUND ABSORPTION)

**3** NC-2 NEOPRENE SPONGE EXTENDS  $\frac{1}{4}$ " BEYOND EDGE OF DOOR ON BOTH SIDES

**4** STAINLESS STEEL THRESHOLD ( $\frac{1}{4}$ " x  $7 \frac{1}{2}$ " x OPENING WIDTH) FACTORY WELDED TO FRAME FOR A 4-SIDED ASSEMBLY (NON DIRECTIONAL FINISH)

**5** ACOUSTIC SEALANT / CAULKING (BY INSTALLER)
- 6** FLOOR / SLAB LINE

**7**  $\frac{1}{4}$ " - 20 T.H.M.S. ADJUSTMENT SCREW

**8** CONDUCTIVE FLOORING BY OTHERS AT **RF SECURE SIDE** AS REQUIRED PER DOOR SWING (DETAIL SHOWN AS REVERSE HANDED)

**9** FULL WIDTH ELECTROMAGNETIC CAULKING, **NOT ACOUSTICAL CAULK** (BY OTHERS)

REV	REVISED	DATE	REVISION NOTES	NAME	DATE
				DRAWN JB	12/15/23
				DETAIL	XX
				S3	
				PROJECT NO: 16XXX	