



- 1**  $\frac{7}{16}$ " x  $\frac{5}{8}$ " RF MONEL SEAL

**2** STAINLESS STEEL THRESHOLD  
( $\frac{1}{4}$ " x  $7\frac{1}{2}$ " x OPENING WIDTH)  
FACTORY WELDED TO FRAME  
FOR A 4-SIDED ASSEMBLY  
(NON DIRECTIONAL FINISH)

**3** ACOUSTIC SEALANT /  
CAULKING (BY INSTALLER)

**4** FLOOR / SLAB LINE
- 5**  $\frac{1}{4}$ " - 20 T.H.M.S.  
ADJUSTMENT SCREW

**6** CONDUCTIVE FLOORING  
BY OTHERS AT **RF SECURE SIDE**  
AS REQUIRED PER DOOR SWING  
(DETAIL SHOWN AS REVERSE HANDED)

**7** FULL WIDTH ELECTROMAGNETIC  
CAULKING, **NOT ACOUSTICAL CAULK**  
(BY OTHERS)

REV	REVISED	DATE	REVISION NOTES	NAME	DATE
				DRAWN	JB 12/15/23
				DETAIL	<div style="border: 1px solid black; border-radius: 50%; width: 40px; height: 40px; display: flex; align-items: center; justify-content: center; margin: 0 auto;"> <span style="font-size: 24px; font-weight: bold;">S1</span> </div>
				PROJECT NO: 16XXX	
				RF SILL DETAIL	