


- 1** FILL SOLID WITH SOUND DEADENING MATERIAL
- 2** CONTINUOUS ACOUSTICAL SEALANT
- 3** SHIM AS REQUIRED TO SUIT ROUGH OPENING
- 4** FACTORY PUNCH AND DIMPLE TRIM FRAME FOR # 8-32 F.H.M.S. @ 24" O.C. TRIM IS SCREWED TO FRAME. REMOVAL & REAPPLICATION OF TRIM FRAME IS BY INSTALLER.
- 5** STUFF 1/4" CLEARANCE GAP WITH INSULATION BY INSTALLER

- 6** THROAT DIMENSION OF FRAME IS NET WALL + 1/8" INSTALLATION CLEARANCE.
 _____ + _____ CLEARANCE= _____
- 7** PUNCH & DIMPLE FOR 1/4" FLAT HEAD SCREW *STAGGERED* _____ PER JAMB _____ PER HEAD. Z & PIPE SPACER @ EACH SCREW LOCATION. NOTE: BOTTOM P & D MUST BE ON DOOR SIDE. (ANCHOR BOLTS FURNISHED BY INSTALLER)
- 8** PRESSURE ANCHOR: 1 BELOW BOTTOM & CENTER HINGE, STRIKE JAMB SIMILAR. LOCATE TO FULLY ENGAGE SURFACE OF STUD




KRIEGER STEEL PRODUCTS
 Pico Rivera, CA
 (562)695-0645

Project No: _____

Date: _____

Drawn By: _____

Detail: 

Sheet: _____