

# Model BD4

## DETAILS<sup>1</sup>

UL-752 <sup>2</sup>	N.I.J. (0108.01)	Weapons Criteria	Shots
Level 4	Type VI	.30-06 Springfield Rifle 180 gr. Pointed Soft Point at 2540 fps	1

## DOWNLOADS

### Generic Frame

DWG File	<a href="http://www.kriegerproducts.com/downloads/cad/dwg/BD4.dwg">http://www.kriegerproducts.com/downloads/cad/dwg/BD4.dwg</a>
DWF File	<a href="http://www.kriegerproducts.com/downloads/cad/dwf/BD4.dwf">http://www.kriegerproducts.com/downloads/cad/dwf/BD4.dwf</a>
PDF File	<a href="http://www.kriegerproducts.com/downloads/cad/pdf/BD4.pdf">http://www.kriegerproducts.com/downloads/cad/pdf/BD4.pdf</a>

## NOTES

- Specification: [http://www.kriegerproducts.com/downloads/doc/KSP\\_BulletAllSpec.doc](http://www.kriegerproducts.com/downloads/doc/KSP_BulletAllSpec.doc)
- This is a pre-engineered model. We custom manufacture to your actual needs.

## LEDGEND

1. Hinge type on tested door for level 1, 2, 3, & 6 is a standard mortise butt hinge. Hinge type on tested door for level 4, 5, 7 & 8 is a Continuous Heavy Duty Hinge, prepared on door only, field drilling and tapping on frame by others.
2. KSP's Bullet Resistant Doors are available with up to 3 hour U/L label. We also offer positive pressure tests in accordance with Standards: U/L 10C and UBC 7-2 and 7-4. (Standard testing restrictions apply)