

Model NC12-30-9155

DETAILS

STC	Weight	Seal ¹	U/L Label ³	Recommended Max. V/L Area	Hinges ²	Threshold
55	22.7	NC12	N/A	N/A	N/A	Alum. or S.S.

TEST REPORT DATA

Report	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	5000
TL91-200	39	39	42	43	45	46	50	50	52	54	56	56	59	60	62	63	64	64

DOWNLOADS

Generic Frame

DWG File	http://www.kriegerproducts.com/downloads/cad/dwg/NC12-30-9155.dwg
DWF File	http://www.kriegerproducts.com/downloads/cad/dwf/NC12-30-9155.dwf
PDF File	http://www.kriegerproducts.com/downloads/cad/pdf/NC12-30-9155.pdf

NOTES

- Doors tested are flush design and 3" thick.
- Specification: http://www.kriegerproducts.com/downloads/doc/KSP_SteelAcousticalDoor.doc
- This is a pre-engineered model. We custom manufacture to your actual needs.

LEDGEND

1. Noise Control Seals and Astragals are KriegerSonic® proprietary design.
2. Hinge type shown on tested door (see options column for alternate hinge). STD = standard mortise butt hinge. C/L = Cam lift hinge. Cam lift hinges are KriegerSonic® proprietary design and are furnished with the door assembly. Cam lift hinges will increase the force required to fully operate a door, this should be considered for facilities with handicap codes.
3. Doors are available with up to 3 hour U/L label. We also offer positive pressure tests in accordance with Standards: U/L 10C and UBC 7-2 and 7-4.