

## Model NC6-225SL-9840

**DETAILS**

| STC | Weight | Seal <sup>1</sup> | U/L Label <sup>3</sup> | Recommended Max. V/L Area | Hinges <sup>2</sup> | Threshold     |
|-----|--------|-------------------|------------------------|---------------------------|---------------------|---------------|
| 40  | 15.5   | NC6               | N/A                    | N/A                       | N/A                 | Alum. or S.S. |

**TEST REPORT DATA**

| Report   | 100 | 125 | 160 | 200 | 250 | 315 | 400 | 500 | 630 | 800 | 1000 | 1250 | 1600 | 2000 | 2500 | 3150 | 4000 | 5000 |
|----------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|
| TL98-426 | 29  | 33  | 37  | 42  | 41  | 41  | 40  | 39  | 36  | 36  | 37   | 36   | 38   | 41   | 44   | 43   | 46   | 46   |

**DOWNLOADS****Generic Frame**

|          |   |
|----------|---|
| DWG File | <a href="http://www.kriegerproducts.com/downloads/cad/dwg/NC6-225SL-9840.dwg">http://www.kriegerproducts.com/downloads/cad/dwg/NC6-225SL-9840.dwg</a> |
| DWF File | <a href="http://www.kriegerproducts.com/downloads/cad/dwf/NC6-225SL-9840.dwf">http://www.kriegerproducts.com/downloads/cad/dwf/NC6-225SL-9840.dwf</a> |
| PDF File | <a href="http://www.kriegerproducts.com/downloads/cad/pdf/NC6-225SL-9840.pdf">http://www.kriegerproducts.com/downloads/cad/pdf/NC6-225SL-9840.pdf</a> |

**NOTES**

- Sliding Man Door includes a manual or power operated track and trolley system.
- Specification: [http://www.kriegerproducts.com/downloads/doc/KSP\\_SteelAcousticalDoor.doc](http://www.kriegerproducts.com/downloads/doc/KSP_SteelAcousticalDoor.doc)
- This is a pre-engineered model. We custom manufacture to your actual needs.

**LEDGEND**

1. Noise Control Seals and Astragals are KriegerSonic® proprietary design.
2. Hinge type shown on tested door (see options column for alternate hinge). STD = standard mortise butt hinge. C/L = Cam lift hinge. Cam lift hinges are KriegerSonic® proprietary design and are furnished with the door assembly. Cam lift hinges will increase the force required to fully operate a door, this should be considered for facilities with handicap codes.
3. Doors are available with up to 3 hour U/L label. We also offer positive pressure tests in accordance with Standards: U/L 10C and UBC 7-2 and 7-4.