

Model NC7-216-8951

DETAILS

STC	Weight	Seal ¹	U/L Label ³	Recommended Max. V/L Area	Hinges ²	Threshold
51	14.4	NC7/A2	ABCDE	CALL	Cam Lift	Alum. or S.S.

TEST REPORT DATA

Report	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	5000
TL89-232	36	40	36	40	45	44	47	47	48	49	50	51	53	54	57	58	57	56

DOWNLOADS

Generic Frame

DWG File	http://www.kriegerproducts.com/downloads/cad/dwg/NC7-216-8951.dwg
DWF File	http://www.kriegerproducts.com/downloads/cad/dwf/NC7-216-8951.dwf
PDF File	http://www.kriegerproducts.com/downloads/cad/pdf/NC7-216-8951.pdf

NOTES

- Doors tested are flush design and 1-3/4" thick.
- Specification: http://www.kriegerproducts.com/downloads/doc/KSP_SteelAcousticalDoor.doc
- This is a pre-engineered model. We custom manufacture to your actual needs.

LEDGEND

1. Noise Control Seals and Astragals are KriegerSonic® proprietary design.
2. Hinge type shown on tested door (see options column for alternate hinge). STD = standard mortise butt hinge. C/L = Cam lift hinge. Cam lift hinges are KriegerSonic® proprietary design and are furnished with the door assembly. Cam lift hinges will increase the force required to fully operate a door, this should be considered for facilities with handicap codes.
3. Doors are available with up to 3 hour U/L label. We also offer positive pressure tests in accordance with Standards: U/L 10C and UBC 7-2 and 7-4.