




Model: SCIF-705-SG3-RF40-VON



Sound Group 3
SCIF Standard



40 dB Shielding
Radio Frequency



STC 45
Acoustical Rating


ADA COMPLIANT

FIRE RATED UP TO 20 MINUTES

1 3/4" THICK DOOR PANEL

SHIPS IN 6 WEEKS

The KriegerSCIF 705 Door and Lock Package meets ICD 705 Sound Group 3 (SG3) requirements for sensitive compartmented information facilities (SCIFs). It provides 40 dB radio frequency (RF) shielding and comes with a Von Duprin exit-only locking device—all in one box.



HM-00013 Mar 2026

Customize Your Package

Contact your Krieger Regional Sales Manager to discuss customizing your 705 Door and Lock Package to meet specific size, configuration, and performance needs. Any customization will result in a longer production time.

Call us at 877.671.7011 or visit KriegerProducts.com to get started.





Tests and Certifications

- Complies with ICD 705 Sound Group 3 requirements for SCIFs.
- Successfully tested and rated to STC 45 (NIC 40 in situ); higher ratings up to STC 55 are available.
- Provides 40 dB RF shielding in the magnetic, electric, planewave, and microwave fields in the frequency range of 1 KHz to 8 GHz.
- Certified for use in installations where TEMPEST standards are required.
- **Radio frequency:** IEEE-299-2006 Standard, NSA 65-6, MIL STD-285, and Division 8 Standard.
- **Acoustical:** ASTM E90, ASTM E336, ASTM E1408, ASTM E413, ASTM A 1008, JUIAF, JAFAN, DCID 6/9, and ICPM 2006-700-7.

Door and Frame Construction

- Slip-in frame design comes in two options to work with any type of wall construction.
- Unique seal system includes Krieger's RF/STC RNC1 (fabric over foam) perimeter seal for superior durability over finger stock gaskets, and an adjustable RNC1 (silicone) door bottom for a tight seal even on uneven floors.
- Features 1¾" thick door panel and can meet all specifications for size, finish, and performance.
- Door panel meets ADA requirements for push/pull maximum force.
- Comes with an ADA-compliant stainless steel threshold with ¼" tapered edge.

Fire Labels and Positive Pressure

- Smoke Labels: Up to 20 minutes

Door Sizes

- This 705 package fits 3'1" x 7'0" openings; complies with ADA door opening size standards.

Hardware

- SCIF assemblies come with three HC30 Cam Lift Hinges: two support hinges and one electrified hinge.
- Comes with a factory mounted, heavy-duty Von Duprin panic bar (98-EO-ALK-F) featuring a latch bolt, alarm, and no exterior trim.
- Krieger's 10-year warranty covers the door and frame. The locking device warranty is covered by the lock manufacturer.

Other Locking Device Options


- Can be configured with a choice of factory mounted 2890C Sargent & Greenleaf or Lockmasters locking device (Type II or Type IV).
- Both locking device options come with a GSA-approved combination digital dial (Kaba X-10).

Finish

- The 705 Door and Lock Package comes prime painted and ready to apply finish paint.

Shipping

- This model ships in 6 weeks.
- Customization is available, but requires a longer lead time; contact us for more information



Everything You Need in One Box


COMPLETE 705 DOOR AND LOCK PACKAGE INCLUDES:

Door Panel Slip-In Frame	Cam Lift Hinges Threshold	Locking Device Closer	Seal System Door Bottom
Installation Bundle			
Installation Instructions	Shop Drawings	EMI Caulk	
Thermafiber Sound Insulation	Anchor Bolts and Fasteners	Complete Set of Metal Shims	




Elevation View – Panic Bar

Single Door



Door Handing Options

KriegerSCIF doors are available in any door handing configuration your project requires.






Frame Detail – Panic Bar

Slip-In With Trim Frame

Krieger's slip-in frame comes in two options to work with wall constructions of varying type and size.

Door Panel

Comes with a typical 1 3/4" thick door panel with a seamless edge on the top and sides, and an adjustable door bottom.





Door Bottom

Adjustable Door Bottom Detail

