


KriegerBullet Level 6 Wood Veener Door

Model: BR-WV-LVL6



ADA
COMPLIANT

FIRE RATED
UP TO 60 MINUTES

2" THICK
DOOR PANEL

The industry-leading KriegerBullet door assembly is engineered to protect personnel and property from bullets and ricochet—with a custom wood veneer finish. This specialty door comes with a UL 752 Level 6 bullet rating, which means it can stop up to 5 shots from a 9 mm submachine gun.



Configurations

Available in single, uneven paired, and double door assemblies; two-panel assemblies come with an astragal or removeable mullion.




Frame

Three-sided frame features innovative slip-in with trim design, Z anchor, nailing straps, T anchor, or punch & dimple frame types.




Door Panel

Typical 2" thick panel with seamless edge on top and sides, and adjustable door bottom. ADA-compliant for push/pull maximum force.




Hinge Options

Hinge(s) are not included with this model. Krieger offers recommended continuous hinge (1 per door) or 5-knuckle butt hinges (3 per door), purchased separately.



Vision Lights

Available with fully customizable vision lights, side lights, and transoms. Bullet-resistant glass UL 752 rating must match the rating for the door assembly.



Wood Finishes

Species and Type	Finish Options
Select the type of wood or species you prefer. Forest Stewardship Council® (FSC®) certified wood is available.	Specify whether you need unfinished or clear coat; for stained finishes, send us a stain sample to ensure a perfect match.

Customize Your Assembly

Contact your Krieger Regional Sales Manager to discuss your project requirements, get a quote, and request full test report data.

Call us at 877.671.7011 or visit KriegerProducts.com to get started.

HM-00013 May 2026





Tests and Certifications

- UL 752 11th Edition Level 6 bullet rating means it can withstand 5 impacts from a 9 mm submachine gun loading 124 grain full metal jacket ammunition shot at 3080 FPS.
- UL 752 is the most widely used and accepted rating system for ballistic-grade materials.
- Meets National Institute of Justice (NIJ) Standard 0108.01 Type IIIA, which can stop up to 5 shots from a .44 Magnum pistol.

Door and Frame Construction

- Choice of frame design includes: slip-in with trim, Z anchor, nailing straps, T anchor, and punch & dimple.
- Constructed with formed, heavy-gauge steel face sheets around a custom engineered steel rib core with interior armor plate.
- Features 2" thick door panel and can meet all specifications for size, finish, and performance; contact us to customize your assembly.
- Three-sided frame design does not require a threshold. Aluminum threshold is available upon request.
- Door panel meets ADA requirements for push/pull maximum force.

Fire Labels and Positive Pressure

- **Up to 60 Minutes:** UL 10C, UBC 7-2, UBC 7-4, 250°, 450°, 650° temperature rise up to 10'0" x 9'10" opening size
- **Smoke Labels:** Up to 20 minutes

Door Sizes


- All KriegerBullet doors are available in standard and custom sizes, including oversized doors.

Hardware

- Hinge(s) are not included with this model. Krieger offers recommended continuous hinge (1 per door) or 5-knuckle butt hinges (3 per door), purchased separately. Contact us for more information.
- Designed to interface with recommended builder's hardware, including latches and locksets, panic devices, security hardware, access controls, and other options.

Wood Veneer Finishes

- Krieger offers a full range of custom wood veneers to perfectly complement your project.
- Select the wood species or type of wood veneer, and whether you need unfinished or clear coat finish.
- If you need a stained finish, send us a stain sample to ensure a perfect match.
- Forest Stewardship Council® (FSC®) certified wood is available.




Vision Lights • Side Lights • Transoms

- Fully customizable vision lights, side lights, and transoms are available.
- Krieger offers tested and certified glass or glass/polycarbonate glazing materials for bullet door assemblies with vision lights, side lights, and/or transoms.
- Bullet glass UL 752 11th Edition rating must match the rating for the door assembly.
- All glass is shipped along with the door assembly to be installed at the job site by your glazer.
- Option to add adjustable blinds in between the panes of glass to control the amount of light and provide added privacy and security.



Elevation View

Single Door



Door Handing Options


KriegerBullet doors are available in any door handing configuration your project requires.






Elevation View

Double Door With Mullion



Door Hanging Options


KriegerBullet doors are available in any door handing configuration your project requires.






Elevation View

Double Door With Astragal



Door Handling Options

KriegerBullet doors are available in any door handing configuration your project requires.






Frame Detail

Slip-In With Trim Frame

Z anchor, nailing straps, T anchor, and punch & dimple frames are also available.

Door Panel


Comes with a typical 2" thick door panel with a seamless edge on the top and sides, and an adjustable door bottom.





Frame Detail


Mullion Detail





Frame Detail

Astragal Detail





Door Bottom

Adjustable Door Bottom Detail

