



- 1  $\frac{1}{4}$ " EMI GLASS w/  $\frac{1}{8}$ " x 1" KSP ELECTROSONIC SEAL INTEGRAL STOP SIDE OF GLASS,  $\frac{1}{8}$ " x  $\frac{1}{2}$ " NEOPRENE GLAZING TAPE AT OPPOSITE SIDE
- 2  $\frac{3}{32}$ " CLEAR LAMINATE GLASS, w/ GLAZING BLOCK &  $\frac{1}{8}$ " x  $\frac{1}{2}$ " NEOPRENE GLAZING TAPE
- 3  $\frac{3}{16}$ " x  $\frac{5}{16}$ " 16 GAUGE GLASS STOP - 304 STAINLESS STEEL,
- 4 18 GAUGE PERFORATED METAL, PRIME PAINTED BLACK (BY KRIEGER)
- 5 SHIM AS REQUIRED TO SUIT ROUGH OPENING (BY INSTALLER)
- 6 REMOVABLE TRIM - FACTORY P&D FOR #8-32 F.H.M.S. @ 24" O.C.
- 7 THROAT DIMENSION OF FRAME IS NET WALL +  $\frac{1}{4}$ " INSTALLATION CLEARANCE
- 8 PUNCH & DIMPLE FOR  $\frac{1}{4}$ " FLAT HEAD SCREW, ANCHORS NOT TO EXCEED 20" O.C. STRAP & PIPE SPACER @ EACH SCREW LOCATION. (ANCHOR BOLTS FURNISHED BY INSTALLER)
- 9 TAPE RF FLANGE TO RF MATERIAL BEFORE COMPLETING DRY WALL. FACE OF FLANGE MUST BE CLEAN, FREE FROM DUST & DIRT. CLEAN WITH SCOTCH BRITE WIRE WHEEL & ALCOHOL

| REV | REVISED | DATE | REVISION NOTES |
|-----|---------|------|----------------|
|     |         |      |                |
|     |         |      |                |
|     |         |      |                |

| NAME     | DATE |
|----------|------|
| DRAWN PM | DATE |
| DETAIL   |      |
| A        |      |

RF 70 dB / STC-52 Window

PROJECT NO: