

## GENERAL HANDLING GUIDE

- Oversized doors and specialty door are very heavy and require precaution when handling. Use the provided lift lugs when moving or handling oversized doors and frames. To prevent denting or damaging the surface of doors and frames be sure to use padding when moving. Avoid resting doors on the corner as this may cause damage.
- Take precaution when handling doors with preinstalled door bottoms. Do not store or slide the doors on the door bottom seal. These door bottoms can damage easily and will affect the performance of the door.
- Wedging these types of doors at any point can damage the bottom seal.
- All paint applied to the doors and frames should be completely cured BEFORE adjusting seals. Please be sure to use Low VOC solvent or water based paint to reduce paint outgassing from breaking down the gasket seal material.
- When handling wood veneer doors on site be sure not to store them outside as this can cause damage to the veneer. They must be stored indoors in a clean and dry environment.
- Due to our uncoupled acoustic door construction there possibility of the door having a slight “pillow” or “balloon” shape. This is a normal condition which requires no repairs.

### Voiding Warranty

- Krieger steel doors that are veneered are not intended for exterior usage. Any such usage on exterior assemblies will void warranty, and relieve Krieger of any duty or responsibilities.
- Natural variations in the color or texture of wood are not to be considered as defects.
- Unsatisfactory appearance caused by handling, job site finishing and installation.
- Any modifications or repairs made to Krieger assemblies without prior authorization from Krieger Specialty Products will void warranty .